

3350MX

Advantages:

- *High performance
- *VESA standard
- *Fan less design
- *Long life time cycle
- *Low power consumption

The 3350MX series is fully compatible with Microsoft® Windows desktop series and Linux O/S; also supported embedded operating systems Windows Embedded Standard and Windows Embedded CE can be use for Home Automation, POS, KIOSK devices and industrial applications.

Chassis design with VESA standard holes for mounted to the rear of LCD monitor, small dimension 95x95x20mm small and slim form factor. The unit with ultra low power consumption 10W only can be fan less design to avoid the noise and dust to extend the life cycle of the computer.



Specifications

Model Type	3350MX
Processor	MSTI PMX-1000 (1.0 GHz)
BIOS	AMI BIOS
Memory	Onboard 512 MB DDR2
VGA	Integrated Graphics Chip/ D-Sub 15-pin
Ethernet	10/100 Mbps LAN (RJ-45 connector) Built-in PXE diskless boot function
USB	3 ports (2 at the front, 1 at rear)
Audio	Mic in and Line out
SD Slot (Note 1.)	1x
Power	DC +5V
Dimensions	95 x 95 x 20 mm
Weight	277 g
Operation Temp	5 ~ 40 °C

Note:

1. SD Slot x 1 (Bootable but hot-swappable not support)